



## HiVis FR PPE2 D/N Rain Jacket

**Fabric:** 280gsm "3 layer bonded into 1" waterproof and breathable fabric, 99% polyester & 1% Anti-static carbon outer laminated to 50% Modacrylic & 50% cotton inner (soft & comfortable against skin), fully seam sealed, HRC2 – ATPV: 8+cal/cm2. 2-way radio loops on front shoulders, Storm flap at centre front with SBS 8# Vislon 2-way heavy duty zipper/plastic slider; Detachable zip off hood with SBS 5# Vislon zipper, elastic cuffs with adjustable sleeve tab & touch tape closure. Twin waist pockets with flap and touch tape closure. Hoop Pattern Bio-Motion "ANS UL-209 FR" Segmented FR Reflective Tape (50 washes) on Body & sleeves. 2 Tone front only.

**Sizes:** XS-6XL

**Colour:**



### FEATURES:



**SUN Protection UPF 40+ - 50+**

DNC garments are tested for UPF (ultraviolet protection factor) in accordance with AS/NZS4399:2017. The level of protection varies depending on the fabric and colour of the garment. 15+, 30+/35+, 40+/50+



**Inherent FR**

Flame Resistance (FR) is naturally occurring in properties of the fibre and won't wash or wear out and are NOT Fireproof. It'll only provide protection against clothing ignition and to self-extinguish almost immediately upon removal of the ignition source.



**PPE2 ATPV: 8+ Cal/cm<sup>2</sup>**

NFPA 70E / ASTM F1959 - Electrical Safety in the Workplace - Personal Protective Equipment (PPE) Category 2, PPE2(HRC2) min ATPV 8 Cal/cm2.



**NENS09:2014**

Selected by Energy Networks Australia, use and maintenance of Personal Protective Equipment (PPE) used to protect people against electrical arc hazards within the Electricity Supply Industry. The recommended minimum ATPV for base garments is PPE (HRC 1) -- 4cal/cm2, and all opening/buttons/press studs/zippers are been covered by FR fabric.



**ISO 14116:2015 (FR)**

Specifies the performance requirements for the limited flame spread properties of all material assemblies and protective clothing to reduce the possibility of the clothing burning when in occasional and brief contact with small flames and constituting a hazard.



**ISO 11612:2015 (FR)**

This clothing is intended to protect the wearer against small splashes of molten metal, short contact with flames, radiant heat from electric arcs, protection for welding and allied processes. It can minimize the possibility of electrical shock by short-term, contact with live electrical conductors up to approximately 100 VDC (Sweat, soiling or other contaminants can affect protection levels).



**EN 1149-5:2008 (Anti-static)**

The latest technology is used in the production of DNC Carbon grid Anti—static 98% Polyester/PU, 2% Carbon, breathable waterproof fabric rain jacket, vest & pants, comply with EN ISO 14116:2008 for FR & BS EN1149-5:2008 for Anti-static.



**HiVis D/N Fabric & Design New AS/NZS 4602.1:2011**

DNC HiVis garments are standard Class F AS/NZS1906.4:2010, Class D/N, AS/NZS 460212011 to meet the requirements of Hi-Vis Safety standards HiVis Fabric & Design of garments, for day and night use.



**Environmentally Friendly Green Dye**

All DNC garment fabric fully complies with Oeko-Tex standard 100 class II for products with direct contact to the skin. It does not contain harmful, non-aromatic amine and does not produce pollution of the environment harmful chemical.



**Waterproof & Breathable**

DNC HiVis Rainwear utilises the latest fabric technology. Not only are they waterproof, but also fully breathable.