3736



HiVis Two Tone Drill Shirt with 3M8906 R/Tape - Long Sleeve

Fabric: 190gsm 100% Cotton Drill
Twin button down flap pocket. Hoop Style 3M8906 R/Tape.

Size: XS-6XL

Colour:

FEATURES:

SUN Protection UPF 40+ - 50+
DNC garments are tested for UPF (ultraviolet protection factor) in accordance with AS 4399:2020. The level of protection varies depending on the fabric and colour of the garment. 15+ good protection, 30+ / 35+ very good protection, 40+ / 50+ excellent protection.

Hi-Vis D/N Fabric & Design AS/NZS 4602.1:2024
DNC Hi-Vis garments are manufactured to comply with new Hi-Vis standard Class F AS/NZS1906.4:2023, Class D/N, AS/NZS 4602.1:2024 to meet the requirements of Hi-Vis safety standards Hi-Vis Fabric & Design of garments, for day and night use.

3M Scotchlite Australia Supply
DNC use 3M Reflective Tape throughout 99% of the Hi-Visibility range. 3M Australia Supply is only provided for distribution to approved 3M Australia Supply Partners with national wide quality guarantee. Check details under product for relevant 3M codes. All 3M Reflective Tape complies with AS/NZS1906.4:2023 for Hi-Vis material. 3M8906 Home wash up to 30 cycles @ 60°C. 3M8910 Home wash up to 50 cycles @ 60°C.

100% Cotton
DNC has an extensive 100% cotton range for a natural feeling garment with Anti-Static and Electrical Protection features.

Anti-Static
The latest technology is used in the production of DNC Carbon Grid Anti-Static jacket and pants, complies BS EN 1149-5:2018. DNC cotton garments containing no metal buttons or zippers are also classified under DNC Anti-Static.

Electrical Protection
DNC cotton made garments containing no metal buttons or zippers and are suitable for use in electrical or gas trades.

Environmentally Friendly Green Dye Oeko-Tex Standard 100 Safe to wear against the skin
All DNC garments use the Green Dye only, except for the Patrol Saint Flame Retardant range. All DNC garment fabric fully complies with Oeko-Tex standard 100 Class II for products with direct contact to the skin in which prohibited to use aromatic amines, sensitizing dyes and cancer risk dyes. Green Dye should meet the following conditions: Does not contain harmful or non-aromatic amine; dye itself, non-carcinogenic, sensitization, acute toxicity; the use of formaldehyde and, after extraction of heavy metals in the following limits; non-environmental hormone; non persistent organic pollutants; does not produce pollution of the environment harmful chemicals; not produce chemicals that pollute the environment; colour fastness and superior to disable the use of dyes.